NANO

1.155

Allowed user weight

130 kg

Suitable for passenger transport

Tested according to ISO 7176-19 (max. user weight 130 kg)



MEYRA GROUP



Vario element


Shapely frame concept


Steering wheel connection


Standard with folding back

Pure design

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Low wear due to high quality attachments

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- Adaptable to functional changes and individual needs of the user through adjustment of the back, seat and chassis
- Extensive equipment assortment for long-term users

FIELD OF USE

- For permanent and long term provision
- For paraplegic provision
- Very good suitability for many disease patterns, even for severely encumbered
- Users without function of the lower extremities (lateral transfer, driven through the handrims)

● ORDER ❍ COST ESTIMATE ❍ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Allowed user weight
130 kg

Suitable for passenger transport
Tested according to ISO 7176-19 (max. user weight 130 kg)

Hints
Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.

ACTIVE

Technical specifications

Seat widths in mm	300/320/340/360/380/400/420/440/460/480/500
Width ready to drive in mm from	Seat width + 170
Seat depth in mm	380/400/420/440/460/480/500
Seat height front/rear in mm	450 to 530/360 to 510
Overall height in mm	Rear seat height + back support height
Back support height in mm	*variable von 250 bis 450 +30mm (15mm Schritte)
Length with footrest in mm	720 - 920 (depending on frame length, wheel size and axle position)
User weight	130 kg
Empty weight from	9,5 kg
Permitted total weight in kg	145 kg
Transport weight	6,5 kg
Rear wheel	600 mm(24 inch) / 635 mm(25 inch) / 660 mm(26 inch)
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

01 Frame

	CODE	DESCRIPTION	ANGLE
❑	346	Standard front frame	80°
❑	347	Compact front frame ⚠ *Nur i.V. mit Rahmeneinzug (C-4950)*	88°

Frame options

	CODE	DESCRIPTION
❑	4959	Without taper frame
❑	4950	Taper frame (20 mm each side)
❑	903	Reinforced castor forks ⚠
❑	2999	*Verstärktes Achsrohr ⚠ *Empfohlen bei Verwendung von Zusatzantrieben*

Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	224	Blue metallic
❑	227	Red metallic
❑	4044	Red matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4922	Metallic green
❑	4919	Silverline

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

*Reflective Stickers

*Die Sticker-Aufbringung bei MEYRA kann als Option ausgewählt werden.

	CODE	DESCRIPTION
❑	2300/2304	*MEYRA Design - Weiss
❑	2301/2304	*MEYRA Design - Schwarz
❑	2302/2304	*MEYRA Design - Tricolore
❑	2303/2304	*MEYRA Design - Regenbogen
❑	2300/2305	*Stripe Design - Weiss
❑	2301/2305	*Stripe Design - Schwarz
❑	2302/2305	*Stripe Design - Tricolore
❑	2303/2305	*Stripe Design - Regenbogen
❑	2306	*Sticker-Aufbringung bei MEYRA ⚠ *Nicht i.V. mit Stripe Design (C-2305)*

ACTIVE

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

02 Seat Width (SW) / Seat Depth (SD)

*Die Sitzbreite entspricht der Breite der Sitzbespannung und wird an den Aussenrohren der Sitzbespannung gemessen. Je nach gewählten Seitenteilen und Armlehnen kann die effektive Sitzbreite breiter als die Sitzbespannungsbreite sein.
Die Rückenbreite (gemessen unten an den Aussenrohren) entspricht der Sitzbespannungsbreite.

Die Sitztiefe wird vom Rückenrohr bis zur Vorderkante der Sitzbespannung gemessen.
Standardmässig ist eine Polstertasche unter der Sitzbespannung enthalten.

		*RAHMEN KURZ (C-351)			*RAHMEN MITTEL (C-352)		*RAHMEN LANG (C-353)	
		C-368	C-615	C-784	C-618	C-619	C-787	C-792
		SD 380mm	SD 400mm	SD 420mm	SD 440mm	SD 460mm	SD 480mm	SD 500mm
C-30	SW 300mm	❑	❑	❑	❑	❑	❑	❑
C-32	SW 320mm	❑	❑	❑	❑	❑	❑	❑
C-34	SW 340mm	❑	❑	❑	❑	❑	❑	❑
C-36	SW 360mm	❑	❑	❑	❑	❑	❑	❑
C-38	SW 380mm	❑	❑	❑	❑	❑	❑	❑
C-40	SW 400mm	❑	❑	❑	❑	❑	❑	❑
C-342	SW 420mm	❑	❑	❑	❑	❑	❑	❑
C-344	SW 440mm	❑	❑	❑	❑	❑	❑	❑
C-46	SW 460mm	❑	❑	❑	❑	❑	❑	❑
C-48	SW 480mm	❑	❑	❑	❑	❑	❑	❑
C-350	SW 500mm	❑	❑	❑	❑	❑	❑	❑

Composite Castor Wheels

		Front Seat Height (FSH) in mm								
	Composite Castor Wheels	450	460	470	480	490	500	510	520	530
C-2480	4" (100x23mm) with integrated lighting	❑	❑	❑	❑	❑	❑	❑		
C-151/908	4" (100x32mm) solid rubber black (250g)	❑	❑	❑	❑	❑	❑	❑		
C-151/909	4" (100x32mm) solid rubber grey (250g)	❑	❑	❑	❑	❑	❑	❑		
C-325/908	5" (125x40mm) solid rubber black (388g)		❑	❑	❑	❑	❑	❑	❑	
C-325/909	5" (125x30mm) solid rubber grey (318g)		❑	❑	❑	❑	❑	❑	❑	
C-327/908	5.5" (142x36mm) soft solid rubber black (570g)			❑	❑	❑	❑	❑	❑	❑
C-327/909	5.5" (142x36mm) soft solid rubber grey (570g)			❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
(S) Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Aluminium Castor Wheels (32mm)

		Front Seat Height (FSH) in mm							
	Aluminium Castor Wheels (32mm)	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**
C-2481	4" (100x32mm) aluminium silver (281g)	❑	❑	❑	❑	❑	❑	❑	
C-2482	5" (125x32mm) aluminium silver (363g)		❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Ⓢ Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Aluminium Castor Wheels (37mm)

		Front Seat Height (FSH) in mm							
	Aluminium Castor Wheels (37mm)	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**
C-2483	4" (100x37mm) silver (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2484	4" (100x37mm) black (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2485	4" (100x37mm) white (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2486	4" (100x37mm) red (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2487	4" (100x37mm) blue (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2488	4" (100x37mm) orange (210g)	❑	❑	❑	❑	❑	❑	❑	
C-2489	5" (125x37mm) silver (285g)		❑	❑	❑	❑	❑	❑	❑
C-2490	5" (125x37mm) black (285g)		❑	❑	❑	❑	❑	❑	❑
C-2491	5" (125x37mm) white (285g)		❑	❑	❑	❑	❑	❑	❑
C-2492	5" (125x37mm) red (285g)		❑	❑	❑	❑	❑	❑	❑
C-2493	5" (125x37mm) blue (285g)		❑	❑	❑	❑	❑	❑	❑
C-2494	5" (125x37mm) orange (285g)		❑	❑	❑	❑	❑	❑	❑

Carbon Castor Wheels (30mm)

		Front Seat Height (FSH) in mm							
	Carbon Castor Wheels (30mm)	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**
C-2495	4" (100x30mm) black (158g)	❑	❑	❑	❑	❑	❑	❑	
C-2496	5" (125x30mm) black (205g)		❑	❑	❑	❑	❑	❑	❑

04 Rear Wheels / Rear Seat Height (RSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Rear Wheels (incl. Tyres and Push Rims)

Weight is indicated per complete wheel (without quick release axle).

RSH (mm)	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT
❑	752	A	Light-Wheel Schwalbe RightRun Light tyres (1" tyre width) Aluminium push rims, black	24"	
❑	2473	A	Blacklight wheel, aluminium, rim/hub/spokes black Schwalbe Marathon Plus tyres (1" width) Aluminium push rims, black	24"	
❑	2466	A	Cross wheel Knobby tyres (1.75" width) Stainless steel push rims	24"	
❑	2461	A	DayLite wheel, aluminium, rim/hub/spokes black Gazelle tyres (1" width) Aluminium push rims, black ⚠ *Maximum user weight 100kg*	24"	
❑	2468	B	DayLite wheel, aluminium, rim/hub/spokes black Speedlite tyres (1" width) Aluminium push rims, black ⚠ *Maximum user weight 100kg*	25"	
❑	2465	A	Six-Star High-pressure tyres (8bar) Aluminium push rims	24"	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear Wheels (without Tyres and Push Rims)

Tyres and push rims must be selected separately. Weight is indicated per wheel (without quick release axle).

RSH (mm)	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C					❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT
❑	651	A	Standard wheels, grey	24"	1465g
❑	2651	A	Standard wheels, black	24"	1465g
❑	848	A	Silverdesign, radial spokes, and high-flange hub	24"	870g
❑	695	A	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black **Empfohlen ab 100 kg Nutzergewicht oder bei dynamischer Fahrweise* *Nicht i.V. mit PU-Bereifung, pannensicher (C-474)* *Nicht i.V. mit Carbolife Greifreifen (C-849, C-850, C-853)*	24"	
❑	695	B	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	25"	
❑	695	C	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	26"	
❑	2470	A	Spinergy LX, rim/hub and 12x4mm spokes black **Nicht i.V. mit PU-Bereifung, pannensicher (C-474)* *Nicht i.V. mit 6° Radsturz (C-454)*	24"	687g
❑	2471	A	Spinergy LX, rim/hub black, 12x4mm spokes white **Nicht i.V. mit PU-Bereifung, pannensicher (C-474)* *Nicht i.V. mit 6° Radsturz (C-454)*	24"	687g
❑	2472	A	Spinergy LX, rim/hub black, 12x4mm spokes orange **Nicht i.V. mit PU-Bereifung, pannensicher (C-474)* *Nicht i.V. mit 6° Radsturz (C-454)*	24"	687g
❑	2469	A	Spinergy CLX, carbon rim, hub/18x3mm spokes black **Nicht i.V. mit PU-Bereifung, pannensicher (C-474)* *Nicht i.V. mit 6° Radsturz (C-454)*	24"	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

05 Tyres

Tyres are made of a rubber compound that may leave permanent or hard-to-remove marks on certain surfaces (plastic, wood, parquet, carpets or rugs). No liability is accepted for abrasion damage. Weight is indicated per tyre.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	496	High-pressure tyre, 8 bar, 1" tyre width	24"	
❑	474	PU tyre, puncture-proof, 1" tyre width, black ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	897	Schwalbe Marathon Plus, puncture-resistant, 1" tyre width, black	24"/25"/26"	500g
❑	363	Schwalbe One, puncture-resistant, 1" tyre width, black	24"	
❑	395	Maxxis VN Master Alpha Protect, 10 bar, puncture-resistant, 1" tyre width, black	24"/25"/26"	

06 Push Rims

Weight is indicated per push rim.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	494	Aluminium, silver anodised ⚠ *NC with Active wheel (C-695)*	24"	344g
❑	487	Aluminium, black anodised	24"	255g
❑	493	Stainless steel, polished	24"/25"/26"	
❑	445	Titanium ⚠ *NC with Silverdesign (C-848)* *NC with standard wheels (C-651, C-2651)*	24"/25"/26"	364g (24")
❑	168	Optigripp-special push rim for tetraplegics	24"	
❑	849	Curve L, aluminium, black anodised, ergonomic profile ⚠ *NC with Active wheel (C-695)*	24"	
❑	850	Curve L Tetra-Grip, aluminium, black, ergonomic profile with anti-slip coating ⚠ *NC with Active wheel (C-695)*	24"	
❑	853	Gekko, aluminium, black anodised, ergonomic profile with integrated, replaceable silicone lip ⚠ *NC with Active wheel (C-695)*	24"	
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*	24"	
❑	692	Push rim spacing, narrow		
❑	693	Push rim spacing, wide		

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

07 Rear Wheels Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	489	Hand and spoke guard, transparent	
❑	2082	Spoke reflectors	
❑	819	Reflectors ⚠ *NC with rear wheels C-752, C-2473, C-2461, C-2468, C-2470, C-2471, C-2472*	

Rear wheel options

	CODE	DESCRIPTION	WEIGHT
❑	880	*Radstandverlängerung 0 oder 73,5mm	
❑	865	Performance Varioblock ⚠ **Nicht i.V. mit 24" und HSH 480mm, 25" und HSH 500mm, 26" und HSH 510mm*	

08 Camber

	CODE	DESCRIPTION
❑	423	0°
❑	447	3°
❑	454	6° ⚠ **Nicht i.V. mit Spinergy (C-2469, C-2470, C-2471, C-2472)* *Nicht i.V. mit Light Druckbremse (C-2595)* *Max. Nutzergewicht 100kg*

09 Center of Gravity

The measurement is taken from the rear edge of the backrest tube to the wheel axle centre, in millimetres.

	PASSIVE						MEDIUM				ACTIVE		
	1 (15mm)	2 (25mm)	3 (35mm)	4 (45mm)	5 (55mm)	6 (65mm)	7 (75mm)	8 (85mm)	9 (95mm)	10 (105mm)	11 (125mm)	12 (135mm)	13 (145mm)
Position	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ **Positionen 11 (125mm), 12 (135mm), 13 (145mm) nicht i.V. mit Rahmen kurz (C-351)*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

10 Footplates

LLL (mm)	310	320	330	340	350	360	370	380	390	400	410	420	430	440	450	460	470	480
A						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
B						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
D	❑	❑	❑	❑	❑													

	CODE	LLL (mm)	DESCRIPTION	WEIGHT
❑	311	A	Footrest, black aluminium, height adjustable	
❑	312	B	Footplate one-piece, black aluminium, height/depth and angle adjustable	
❑	128/312	D	Aluminum footrest in black, height/depth and angle adjustable with shortened lower leg length ⚠ *For lower leg lengths from 310 - 350mm*	
❑	76	C	*Fussplatte durchgehend aus Aluminium in schwarz, höhenverstellbar und nach hinten hochklappbar ⚠ **Nicht i.V. mit Kompatkvorderrahmen (C-347)* *Nicht i.V. mit Rahmeneinzug und SB < 380mm ; Ohne Rahmeneinzug und SB < 340mm* *Nicht i.V. mit 5.5" Lenkräder (C-327/908, C-327/909)*	
❑	4313	A	LED footrest made of sturdy aluminum in black continuous, height / depth and angle adjustable ⚠ *i.C. with CODE 4959 from SW 360mm* *i.C. with CODE 4950 from SW 400mm*	

Footplates Accessories

	CODE		WEIGHT
❑	359	Calf strap	

11 Backrest

Backrest Height (RH)

*Der Rückenbezug ist über Klettbänder anpassbar, und die Rückenhöhe kann ±30mm in 15mm Schritten verstellt werden.

	C-620	C-626	C-631	C-632	C-633
	250mm	300 mm	350mm	400 mm	450mm
Backrest height	❑	❑	❑	❑	❑

ACTIVE

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

*Rückenhöhe Optionen

	CODE	DESCRIPTION	WEIGHT
❑	2314	*Rückenhöhe +45 mm (15 mm Schritte) einstellbar ⚠ *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	

Backrest Angle

The backrest angle is measured relative to the seat surface: 90° = upright; <90° = tilted forward; >90° = tilted backward.

	Position A	Position B	Position C	Position D
	95°	90°	85°	80°
Backrest Angle	❑	❑	❑	❑

Back unit options

	CODE	DESCRIPTION	WEIGHT
❑	2310	*Rückenrohre ausgestellt, 15mm pro Seite ⚠ *Nicht i.V. mit RH < 400mm und Schiebegriffe kurz (C-410)* *Nicht i.V. mit RH < 350mm und ohne Schiebegriffe (C-411)* *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	
❑	2311	*Rückenrohre ausgestellt, 25mm pro Seite ⚠ *Nicht i.V. mit RH < 400mm und Schiebegriffe kurz (C-410)* *Nicht i.V. mit RH < 350mm und ohne Schiebegriffe (C-411)* *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	
❑	2312	*Rückenrohre eingezogen, 15mm pro Seite ⚠ *Nicht i.V. mit RH < 400mm und Schiebegriffe kurz (C-410)* *Nicht i.V. mit RH < 350mm und ohne Schiebegriffe (C-411)* *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	
❑	2313	*Rückenrohre eingezogen, 25mm pro Seite ⚠ *Nicht i.V. mit RH < 400mm und Schiebegriffe kurz (C-410)* *Nicht i.V. mit RH < 350mm und ohne Schiebegriffe (C-411)* *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Upholstery

	CODE	DESCRIPTION	WEIGHT
❑	235	Textile, black	
❑	292	Mesh fabric, breathable, black	
❑	593	Without backrest cover	

Backrest Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	2002	Back cover 20 mm wider	
❑	2003	Back cover 40 mm wider	

Backrest Accessories

	CODE	DESCRIPTION	WEIGHT
❑	2032	ErgoSeat Pro thoracic pads, small, pair	

12 Ride System Back

Please specify the CODE from the RIDE order sheet:

13 Push Handles

	CODE	DESCRIPTION	WEIGHT
❑	411	Backrest without push handle	
❑	410	*Schiebegriffe, kurz (±15mm höheneinstellbar)	
❑	141	Push handles, swiveling	
❑	502	Height-adjustable push handles, mounted on back tube, steplessly adjustable up to 150mm ⚠ *Nicht i.V. mit Armlehnenrohr (C-24)*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

14 Arm Supports and Arm Pads

*Je nach gewählten Seitenteilen und Armlehnen kann die effektive Sitzbreite breiter als die Sitzbespannungsbreite sein.

Clothes and Mudguards

	CODE	DESCRIPTION	WEIGHT
❑	783	*Radspritzschutz, Carbon, fest verschraubt (Radüberdeckung 35mm)	
❑	100	*Radspritzschutz, Aluminium schwarz, fest verschraubt (Radüberdeckung 35mm)	
❑	98	*Radspritzschutz, Aluminium schwarz, fest verschraubt (Radüberdeckung 50mm)	

*Seitenteile und Armlehnen Optionen

	CODE	DESCRIPTION	WEIGHT
❑	11	Side guard removable ⚠ *only i.c. with CODE 100 or 783*	
❑	2903	Sideguard holder aluminum black reinforced	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

15 Seat Cushions

	CODE	DESCRIPTION	WEIGHT
❑	560	Seat cushion, 30mm	
❑	561	Seat cushion, 60mm	
❑	7199	Netti Contour Breathable 3D cover	
❑	562	Velcro strip on seat belt	

Seat Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	833	Safety belt (metal buckle)	

16 Ride System Seat

Please specify the CODE from the RIDE order sheet:

17 Brakes

	CODE	DESCRIPTION	WEIGHT
❑	305	Pressure brake (push to lock)	
❑	2595	Light pressure brake, aluminium	
❑	652	Pressure brake, brake lever cranking near the side panel	

Brake Options

	CODE	DESCRIPTION	WEIGHT
❑	986	Brake lever extension ⚠ *Only with pressure brake (C-305)*	
❑	681	Brake lever extension, foldable ⚠ **Nur i.V. mit Druckbremse, Kröpfung seitenteilnah (C-652)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

18 Options

Anti-tippers

	CODE	DESCRIPTION	WEIGHT
❑	728	Anti-tippers, pair, swing-away ⚠ *Nicht i.V. mit HSH < 380mm* *Nicht i.V. mit Kipphilfe (C-309)*	
❑	729	Anti-tipper, left, swing-away ⚠ *Nicht i.V. mit HSH < 380mm* *Nicht i.V. mit Kipphilfe (C-309, C-4930)*	
❑	730	Anti-tipper, right, swing-away ⚠ *Nicht i.V. mit HSH < 380mm* *Nicht i.V. mit Kipphilfe (C-309, C-4931)*	

Tipping Aid

	CODE	DESCRIPTION
❑	309	Tipping aid, pair ⚠ *NC with anti-tippers (C-728, C-729, C-730)*
❑	4930	Tipping aid, left, swing-away ⚠ *NC with anti-tippers (C-728, C-729)*
❑	4931	Anti-tipper, right, swing-away ⚠ *NC with anti-tippers (C-728, C-730)*

Crutch holder

	CODE	DESCRIPTION
❑	970	Crutch holder ⚠ *Only with tipping-aid (C-309, C-4930, C-4931)*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	



18 Code 4930



14 Code 100



10 Code 141



08 Code 305



02 Code 346



04 Code 651




08 Code 652



08 Code 681




18 Code 729



06 Code 849



06 Code 850



08 Code 2595



15 Code 4312



18 Code 4930




14 Code 98



14 Code 24



15 Code 76



15 Code 311



10 Code 410




15 Code 312




03 Code 327



10 Code 411




05 Code 423



05 Code 447



05 Code 454




02 Code 4959



12 Code 7361



14 Code 748



00 Code 418