NANO S

1.157

Allowed user weight

130 kg



MEYRA GROUP



Optimized unlocking of the leg support for users with limited hand and/or upper body function



Shapely frame concept



Side panel with height-adjustable armrest to be operated with one hand



Double cross brace for rigid frame-like ride performance

Designed to swing

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Low wear due to high quality attachments
- High part compatibility

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- Adaptable to functional changes and individual needs of the user through adjustment of the back, seat and chassis
- Extensive equipment assortment for long-term users
- Stabilization and mobilization of users with neurological diseases, through good support while sitting and low weight a.s.o.
- Due to straight forward construction and swivelling, removable leg supports close approach to everyday objects as well as therapeutic motion trainers possible without any problems
- Folding mechanism for independent loading into a car

FIELD OF USE

- For permanent and long term provision
- For paraplegic provision
- Very good suitability for many disease patterns, even for severely encumbered
- Users without function of the lower extremities (lateral transfer, driven through the handrims)
- With neurological diseases
- For users with remaining walking and standing abilities (standing transfer)

● ORDER ❍ COST ESTIMATE ❍ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:



Allowed user weight
130 kg

Hints
Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.

ACTIVE

Technical specifications

Seat widths in mm	320/340/360/380/400/420/440/460/480
Width ready to drive in mm from	480/500/520/540/560/580/600/620/640/660/680
Seat depth in mm	380/400/420/440/460/480/500
Seat height front/rear in mm	450 to 550 / 360 to 510
Overall height in mm	Rear seat height + back support height
Back support height in mm	*variable von 250 bis 450 +30mm (15mm Schritte)
Length with footrest in mm	835 - 995 (depending on frame length, wheel size and axle position)
User weight	130 kg
Empty weight from	from 10 kg
Permitted total weight in kg	145 kg
Transport weight	from 6,5 kg
Rear wheel	600 mm(24 inch) / 635 mm(25 inch) / 660 mm(26 inch)
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

01 Seat width / Seat depth

	Frame short (C-351)			Frame medium (C-352)		Frame large (C-353)	
	(C-368)	(C-615)	(C-784)	(C-618)	(C-619)	(C-787)	(C-792)
Seat width/Seat depth	**SD 380 mm**	**SD 400 mm**	**SD 420 mm**	**SD 440 mm**	**SD 460 mm**	**SD 480 mm**	**SD 500 mm**
SW 320 mm (C-32)	❑	❑	❑	❑	❑	❑	❑
SW 340 mm (C-34)	❑	❑	❑	❑	❑	❑	❑
SW 360 mm (C-36)	❑	❑	❑	❑	❑	❑	❑
SW 380 mm (C-38)	❑	❑	❑	❑	❑	❑	❑
SW 400 mm (C-40)	❑	❑	❑	❑	❑	❑	❑
SW 420 mm (C-342)	❑	❑	❑	❑	❑	❑	❑
SW 440 mm (C-344)	❑	❑	❑	❑	❑	❑	❑
SW 460 mm (C-46)	❑	❑	❑	❑	❑	❑	❑
SW 480 mm (C-48)	❑	❑	❑	❑	❑	❑	❑

⚠ *Seat width measured from the outer edge of the frame tube to the outer edge of the frame tube*
Seat depth measured from the inner edge of the back tube to the end of the seat cover

02 Frame options

	CODE	DESCRIPTION
❑	721	Transport eyelet for vehicle-side attachment of the wheelchair ⚠ *Not in conjunction with CODE 818 fold down backrest*
❑	903	Reinforced castor forks ⚠

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

03 Seat height front (FSH) in combination with plastic castor (without seat cushion)

Please select your desired seat height by selecting a possible combination of seat height and wheel size. The max permissible seat height difference between front and rear seat height is 100 mm!

		Front Seat Height (FSH) in mm										
Code/Art.	**Castor**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
151/908	Ø 100 Solid rubber black	❑	❑	❑	❑	❑	❑	❑				
151/909	Ø 100 Solid rubber grey	❑	❑	❑	❑	❑	❑	❑				
325/908	Ø 125 Solid rubber black		❑	❑	❑	❑	❑	❑	❑			
325/909	Ø 125 Solid rubber grey		❑	❑	❑	❑	❑	❑	❑			
327/908	Ø 142 Soft-solid rubber black			❑	❑	❑	❑	❑	❑	❑		
327/909	Ø 142 Soft-solid rubber grey			❑	❑	❑	❑	❑	❑	❑		
161/909	Ø 175 puncture proof gray							❑	❑	❑	❑	
645/909	Ø 180 pneumatic tires gray							❑	❑	❑	❑	❑

⚠ *Measured from the ground to the upper edge of the frame tube*

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Seat height front in combination with aluminium castor (without seat cushion)

		Front Seat Height (FSH) in mm								
Code	**Castor**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
2483	Ø 100 x 37 mm, Silver	❑	❑	❑	❑	❑	❑	❑		
2484	Ø 100 x 37 mm, Black	❑	❑	❑	❑	❑	❑	❑		
2485	Ø 100 x 37 mm, White	❑	❑	❑	❑	❑	❑	❑		
2486	Ø 100 x 37 mm, Red	❑	❑	❑	❑	❑	❑	❑		
2487	Ø 100 x 37 mm, Blue	❑	❑	❑	❑	❑	❑	❑		
2488	Ø 100 x 37 mm, Orange	❑	❑	❑	❑	❑	❑	❑		
2489	Ø 125 x 37 mm, Silver		❑	❑	❑	❑	❑	❑	❑	
2490	Ø 125 x 37 mm, Black		❑	❑	❑	❑	❑	❑	❑	
2491	Ø 125 x 37 mm, White		❑	❑	❑	❑	❑	❑	❑	
2492	Ø 125 x 37 mm, Red		❑	❑	❑	❑	❑	❑	❑	
2493	Ø 125 x 37 mm, Blue		❑	❑	❑	❑	❑	❑	❑	
2494	Ø 125 x 37 mm, Orange		❑	❑	❑	❑	❑	❑	❑	
2480	Ø 100 x 37 mm, Lightwheel Black	❑	❑	❑	❑	❑	❑	❑		
2481	Ø 100 x 37 mm, castor silver	❑	❑	❑	❑	❑	❑	❑		
2482	Ø 125 x 32 mm, caster silver		❑	❑	❑	❑	❑	❑	❑	

⚠ *Measured from the ground to the upper edge of the frame tube*

Seat height front in combination with carbon castor (without seat cushion)

		Front Seat Height (FSH) in mm								
Code	**Castor**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
2495	Ø 100 x 30 mm, Black	❑	❑	❑	❑	❑	❑	❑		
2496	Ø 125 x 30 mm, Black		❑	❑	❑	❑	❑	❑	❑	

⚠ *Measured from the ground to the upper edge of the frame tube*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

04 Rear wheel (only rim) i.C. with seat height (tyres CAT 07 and handrims CAT 06)

RSH (mm)	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C					❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø
❑	651	A	Standard wheel, incl. quick release axle (pair)	24"
❑	2651	A	Standard wheel black, incl. quick release axle (pair) *not i.c. with drum brake CODE 706*	24"
❑	706	A	Drum braked wheel with radial spokes and drum brake for accompanying person *Only i.c. with push handles CODE 502* *only i.c. with CODE 423 wheel camber 0°* *only i.c. with side panels CODE 98, 81, 84 or 748*	24"
❑	848	A	SILVERDESIGN with radial spokes and high flange rim incl. quick-release axle (pair)	24"
❑	695	A	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black *Recommended from 100 kg user weight or for dynamic driving* *not in conjunction with Carbolife push rims CODE 849, 850, 853* *not in conjunction with PU tires CODE 474*	24"
❑	695	B	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black *Recommended from 100 kg user weight or for dynamic driving* *not i.c. with. Carbolife push rims CODE 849, 850, 853*	25"
❑	695	C	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black *Recommended from 100 kg user weight or for dynamic driving* *not i.c. with. Carbolife push rims CODE 849, 850, 853*	26"
❑	2469	A	Spinergy CLX, carbon rear wheel, spokes and hub black *not in conjunction with PU tires CODE 474*	24"
❑	2470	A	Spinergy LX, aluminum rear wheel, spokes, rim and hub black *not in conjunction with PU tires CODE 474*	24"
❑	2471	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes white *not in conjunction with PU tires CODE 474*	24"
❑	2472	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes orange *not in conjunction with PU tires CODE 474*	24"

Seat height data without seat cushion

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear wheel i.c. with seat height (incl. tyre and handrim)

RSH (mm)	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C					❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø
❑	2465	A	Six-Star incl. 8 bar high pressure tires and aluminum handrims (pair)	24x1"
❑	752	A	Lightwheel incl. RightRun Light tyres and aluminum handrim black ⚠ *only i.c. with 0° wheel camber CODE 423* *not i.c. with transport lug CODE 721* *Recommended up to max. 90kg user weight*	24"
❑	2473	A	Blacklight aluminum rear wheel, incl. Schwalbe Marathon Plus tyres and aluminum push rims, rim, hub and spokes black	24x1"
❑	2466	C	Cross-Rad incl. coarse studded tyres and stainless steel handrims (pair) ⚠ *Recommendation: CODE 98 side panel*	24x1.75"
❑	2461	A	Day-Lite aluminum rear wheel, rim, hub and spokes black. Black aluminum handrim and black MBL Gazelle tires. ⚠ *max. user weight 100kg*	24x1"
❑	2468	B	Day-Lite aluminum rear wheel, black rim, hub and spokes, black aluminum handrim and black MBL Speedlite tyres. ⚠ *max. user weight 100kg*	25x1"

⚠ *Seat height data without seat cushion*

Horizontal rear wheel position (center of gravity)

	PASSIV (Pos./mm)			MEDIUM (Pos./mm)			ACTIVE (Pos./mm)			
	1/35	2/45	3/57	4/69	5/81	6/93	7/105	8/115	9/135	10/147
Position	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ *Axle position in mm (rear edge of back tube to center of axle)*
ACTIVE position i.c. with frame short CODE 351 not mountable

05 Camber

	CODE	DESCRIPTION
❑	423	0° wheel camber
❑	447	3°-wheel camber (track adjustable)

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

06 Push Rims

	CODE	DESCRIPTION	Ø
❑	493	Stainless steel, polished	24"/25"/26"
❑	487	Aluminium, black anodised	24"
❑	494	Aluminium, silver anodised ⚠ *Not i.c. with Active-Wheel CODE 695*	24"
❑	445	Titanium, with 6 brackets ⚠ *Only in combination with Aktiv-Wheel CODE 695 or Spinergy-Wheel CODE 2469, 2470, 2471, 2472*	24"/25"/26"
❑	168	Optigripp-special push rim for tetraplegics	24"
❑	849	Curve L, aluminum black anodised, ergonomic handrim profile, H 31 mm	24"
❑	850	Curve L Tetra Grip, anti-slip coated, aluminum, suitable for quadriplegics, ergonomic handrim profile, H 31 mm	24"
❑	853	Gekko, aluminum black anodized with replaceable ruber lip, ergonomic hand rim profile, H 31mm	24"

Push Rim Options

	CODE	DESCRIPTION	
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*	24"
❑	692	Handrim distance narrow	24"
❑	693	Handrim distance far	24"

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

07 Tyres

	CODE	DESCRIPTION	Ø		
❑	474	PU-tyres, puncture safe black ⚠ *Not in conjunction with active wheel CODE 695*	24x1"		
❑	496	Pneumatic tires 8 bar	24x1"	25x1"	26x1"
❑	395	Maxxis VN Master Alpha Protect tyre black, puncture resistant, 10 bar	24x1"	25x1"	26x1"
❑	897	Schwalbe Marathon Plus Evolution tyre, puncture resistant	24x1"	25x1"	26x1"
❑	363	Schwalbe ONE tyre, no profile, puncture resistant	24x1"		

Note: Tyres consist of a rubber compound which may leave permanent marks or be hard to remove from some surfaces (e.g. plastic, wooden or parquet flooring, rugs and carpets).

We cannot accept liability for any abrasion damage to flooring.

08 Brakes

	CODE	DESCRIPTION
❑	305	Pressure brake for user
❑	2595	Light scissor brake made of aluminium, swivelling away
❑	652	Pressure brake, brake lever cranking near the side panel ⚠ *not i.c. with side panel CODE 81 and side panel CODE 84*
❑	986	Brake lever extension ⚠ *Only with pressure brake (C-305)*
❑	681	Brake lever extension, foldable ⚠ **Nur i.V. mit Druckbremse, Kröpfung seitenteilnah (C-652)*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

09 Backrest height (BH)

	Backrest height in mm				
	(C-620)	(C-626)	(C-631)	(C-632)	(C-633)
DESCRIPTION	**250**	**300**	**350**	**400**	**450**
The backrest height can be subsequently adjusted by +30mm in 15mm increments	❑	❑	❑	❑	❑

⚠ *With CODE 502 subsequent height adjustment not possible*
Measured from top edge of seat tube to top edge of back tube

Backrest Angle

Pos. A	Pos. B	Pos. C	Pos. D
95°	**90°**	**85°**	**80°**
❑	❑	❑	❑

⚠ *The smaller the angle, the more the back is inclined towards the seat*

Backrest variants

	CODE	DESCRIPTION
❑	2002	Back cover 20 mm wider ⚠ *only i.c. with CODE 235 textile black or 292 mesh, breathable, black*
❑	2003	Back cover 40 mm wider ⚠ *only i.c. with CODE 235 textile black or 292 mesh, breathable, black*
❑	593	Without backrest cover ⚠ *recommended when using RIDE back systems*

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

10 Backrest

Standard 90° to the seat
Adjustable angle and lockable
Backrest angle: -5°/ +5°/ + 10°

	CODE	DESCRIPTION
❑	410	Back with push handle short, height adjustable +/- 15mm
❑	411	Backrest without push handle
❑	502	Backrest with push handle mounted to the frame tube, continuously height adjustable to 150 mm
❑	141	Push handles, swiveling
❑	2310	Backrest tubes extended 15mm per side ⚠ *In conjunction with Push handle CODE 410 from BH 400mm* *in conjunction without push handle CODE 411 from RH 350mm* *not in conjunction with push handle CODE 502.*
❑	2311	Backrest tubes extended 25mm per side ⚠ *In conjunction with Push handle CODE 410 from BH 400mm* *in conjunction without push handle CODE 411 from RH 350mm* *not in conjunction with push handle CODE 502.*
❑	2312	Backrest tubes retracted 15mm per side ⚠ *In conjunction with Push handle CODE 410 from BH 400mm* *in conjunction without push handle CODE 411 from RH 350mm* *not in conjunction with push handle CODE 502.*
❑	2313	Backrest tubes retracted 25mm per side ⚠ *In conjunction with Push handle CODE 410 from BH 400mm* *in conjunction without push handle CODE 411 from RH 350mm* *not in conjunction with push handle CODE 502.*

⚠ *CODE 2310 - 2313 only from back height 350 mm*

Backrest options

	CODE	DESCRIPTION
❑	818	Backrest can be folded forward onto the seat ⚠ *Not in conjunction with CODE 721 Transport eyelet*
❑	2032	ErgoSeat Pro thoracic pads, small, pair ⚠ *Recommended at back height 300 - 400 mm*
❑	238	Stabilising bracket for the back support, folding ⚠ *Not i.c. with push handles CODE 502* *from SW 320mm*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Back-belt variants

	CODE	DESCRIPTION
❑	235	Textile black
❑	292	Mesh fabric, breathable, black

11 Ride System Back

Please specify the CODE from the RIDE order sheet:

12 Seat Cushions

	CODE	DESCRIPTION
❑	560	Seat cushion 30 mm
❑	561	Seat cushion 60 mm
❑	7199	Netti Contour Breathable 3D cover
❑	562	Velcro strip on seat belt

13 Ride System Seat

Please specify the CODE from the RIDE order sheet:

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

14 Arm Supports and Arm Pads

1 = fixed screwed 2 = swivel up 3 = detachable 4 = lockable 5 = height-adjustable armrest 6 = with wheel cover

	CODE	DESCRIPTION	FUNCTIONS
❑	748	Side guard made of aluminium in black with cold protection insert ⚠ *incl. height adjustable armrest (screwed)*	1,5,6
❑	100	Side guard made of aluminium in black with cold protection insert ⚠ *incl. mudguard 35mm*	1,6
❑	783	Carbon fiber side guard ⚠ *incl. mudguard 35mm*	1,6
❑	98	Side guard made of aluminium in black with cold protection insert ⚠ *incl. mudguard 50mm*	1,6
❑	81	Side guard, armrest short, height adjustable with one hand operation ⚠ *Possible from HSH 450 mm* *not in conjunction with. Brake CODE 652* *only possible up to drive wheel position 7*	2,3,4,5
❑	84	Side guard, armrest long, height adjustable with one hand operation ⚠ *Possible from HSH 450 mm* *not in conjunction with. Brake CODE 652* *only possible up to drive wheel position 7*	2,3,4,5

Side guard options

	CODE	DESCRIPTION
❑	11	Side guard removable ⚠ *only i.c. with CODE 100 or 783*
❑	2903	Sideguard holder aluminum black reinforced ⚠ *not in conjunction with Removable side panel CODE 11* *not in conjunction with Seitenteil CODE 81 und 84*

15 Leg supports and footrests

	CODE	DESCRIPTION
❑	293	Upper leg support removable and swivels away, front frame angle 84°
❑	759	Upper leg support CODE 293, only mounted on the left
❑	760	Upper leg support CODE 293, mounted only on the right
❑	94	Without leg supports and footrest

⚠ *The difference between the seat height at the front and the lower leg length must be at least 50 mm*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Footrests

LLL (mm)	380	390	400	410	420	430	440	450	460	470	480
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	LLL (mm)	DESCRIPTION
❑	312	A	Footrest continuous made of sturdy aluminum profile in black folds up, height and angle adjustable
❑	311	A	Footrest continuous aluminum in black fold up, height and angle adjustable
❑	4313	A	LED footrest made of sturdy aluminum in black continuous, height / depth and angle adjustable ⚠ *ab SB 360mm
❑	808	A	Single footplates made of aluminium in black, foldable, depth and angle adjustable
❑	359		Calf belt

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

16 Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	224	Blue metallic
❑	227	Red metallic
❑	4044	Red matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4922	Metallic green
❑	4919	Silverline

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

17 Frame design

	CODE	DESCRIPTION	COLOUR
❑	2300	Reflective Sticker ⚠ *only in conjunction with a sticker design*	white
❑	2301	Reflective Sticker ⚠ *only in conjunction with a sticker design*	black
❑	2302	Reflective Sticker ⚠ *only in conjunction with a sticker design*	Tricolore
❑	2303	Reflective Sticker ⚠ *only in conjunction with a sticker design*	Rainbow

Sticker design

	CODE	DESCRIPTION
❑	2304	MEYRA Design ⚠ *only in conjunction with a frame design*
❑	2305	STRIPE Design ⚠ *only in conjunction with a frame design*
❑	2306	Sticker applied at MEYRA. ⚠ *only i.c. with the colours white, black and tricolore and MEYRA Design*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

18 Options

Hand and spoke guard

	CODE	DESCRIPTION
❑	489	Transparent ⚠ *Not in combination with Spinergy-Wheel CODE 2469, 2470, 2471, 2472*

Support castors

	CODE	DESCRIPTION
❑	691	Anti tipper, 1 pair, swivel under the seat (recommended) ⚠ *Not in conjunction with CODE 309* *from RSH 380mm*
❑	712	Anti tipper, mounted on the left, swivels under the seat ⚠ **Nicht i.V. mit Auftrittrohr CODE 309/4930* *ab HSH 380mm*
❑	713	Anti tipper, mounted on the right, swivels under the seat ⚠ **Nicht i.V. mit Auftrittrohr CODE 309/4931* *ab HSH 380mm*

Pedal tubes

	CODE	DESCRIPTION
❑	309	Pedal caps (1 pair) ⚠ *not i. c. with CODE 1/712/713 Support castor(s)*
❑	4930	Pedal cap, mounted left ⚠ *not i. c. with CODE 691/712 Support castor(s)*
❑	4931	Pedal cap, mounted right ⚠ *not i. c. with CODE 691/713 Support castor(s)*

Other accessories

	CODE	DESCRIPTION
❑	833	Safety belt (metal buckle)
❑	970	Crutch holder ⚠ *Only i.c.w. pedal tube Code 309/4930/4931*
❑	819	Reflectors ⚠ *Not in conjunction with CODE 752, 2473, 2461 and 2468*


☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	
❑	2082	Spoke reflectors	



14 Code 81



14 Code 84



14 Code 98



14 Code 100



10 Code 141



15 Code 293



08 Code 305



10 Code 410



00 Code 418



00 Code 419



08 Code 652



08 Code 681



01 Code 691




18 Code 729



14 Code 748



14 Code 783



08 Code 2595



15 Code 4312



18 Code 4930