FEMTO S

1.186

Allowed user weight

130 kg

Suitable for passenger transport



MEYRA GROUP



Highly stable cross-foldable frame and sleek design



Easy and precise alignment for straight-line driving



Angle adjustable backrest as standard



Legrest lever operable with 1 finger: ideal for users with limited hand function

Fuse Together

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Little wear and proneness to repair through integral design of the frame and the quality of the attachment components

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- Adaptable to functional changes and individual needs of the user through adjustment of the back, seat and chassis
- Extensive equipment assortment for long-term users
- Compact sitting, driving and transport through the optimal frame design
- Adjustable seat and back strap, individually adjustable back height
- Optimum mobility traits: lighter, sportier, easier to tilt and turn

FIELD OF USE

- For permanent and long term provision
- Very good suitability for many disease patterns, even for severely encumbered
- Armrest, height-adjustable, swing-away and removable

● ORDER ❍ COST ESTIMATE ❍ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Standard configuration

- Plastic castor
- Aluminum rear wheel
- Camber 0°
- High-pressure tires
- Stainless steel push rims
- Pressure brake (push to lock)
- Backrest Angle
- Black textile backrest cover
- Push handle short
- Plastic side guard
- Plastic base plates
- Frame Colours

Allowed user weight

130 kg

Suitable for passenger transport

Hints

You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

ACTIVE

Technical specifications

Seat widths in mm	*320 - 520 in 20mm Schritten
Total width in mm	Seat width + 180
Width folded in mm from	*290 bei Radsturz 1° / 330 bei Radsturz 3°
Seat depth in mm	*340 - 500 in 20mm Schritten
Seat height front/rear in mm	425 bis 560 / 390 bis 530
Overall height in mm	Rear seat height + back support height
Back support height in mm	Adjustable from 250 to 500 in 15mm steps
Arm support height in mm	ca. 170 - 245
Length with footrest in mm	880 - 1030 (depending on frame length, wheel size and axle position)
User weight	130 kg
Empty weight from	9,5 kg
Permitted total weight in kg	145 kg
Transport weight	7,4 kg
Rear wheel	600 mm (24") / 635 mm (25") / 660 mm (26")
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

01 Frame and Legrests

	CODE	DESCRIPTION
❑	93	70° legrests, swing-away and detachable
❑	293	80° legrests, swing-away and detachable
❑	94	Without legrests

Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	224	Blue metallic
❑	227	Red metallic
❑	4044	Red matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4919	Silverline
❑	4922	Metallic green

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

02 Seat Width (SW) / Seat Depth (SD)

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Seat depth is measured from the front of the backrest tube to the front edge of the seat upholstery.

		C-394	C-366	C-368	C-615	C-784	C-618	C-619	C-787	C-792
		SD 340mm	SD 360mm	SD 380mm	SD 400mm	SD 420mm	SD 440mm	SD 460mm	SD 480mm	SD 500mm
C-32	SW 320mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-34	SW 340mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-36	SW 360mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-38	SW 380mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-40	SW 400mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-342	SW 420mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-344	SW 440mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-46	SW 460mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-48	SW 480mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-350	SW 500mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-952	SW 520mm	❑	❑	❑	❑	❑	❑	❑	❑	❑

03 Castor Wheels / Front Seat Height (FSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Composite Castor Wheels

		Front Seat Height (FSH) in mm											
	Composite Castor Wheels	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**	**560**
C-2480	4" (100x23mm) with integrated lighting	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-151/908	4" (100x32mm) solid rubber black (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-151/909	4" (100x32mm) solid rubber grey (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-325/908	5" (125x40mm) solid rubber black (388g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-325/909	5" (125x30mm) solid rubber grey (318g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-327/908	5.5" (142x36mm) soft solid rubber black (570g)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-327/909	5.5" (142x36mm) soft solid rubber grey (570g)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Aluminium Castor Wheels (32mm)

		Front Seat Height (FSH) in mm											
	Aluminium Castor Wheels (32mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2481	4" (100x32mm) aluminium silver (281g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2482	5" (125x32mm) aluminium silver (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Aluminium Castor Wheels (37mm)

		Front Seat Height (FSH) in mm										
	Aluminium Castor Wheels (37mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2483	4" (100x37mm) silver (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2484	4" (100x37mm) black (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2485	4" (100x37mm) white (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2486	4" (100x37mm) red (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2487	4" (100x37mm) blue (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2488	4" (100x37mm) orange (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2489	5" (125x37mm) silver (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2490	5" (125x37mm) black (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2491	5" (125x37mm) white (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2492	5" (125x37mm) red (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2493	5" (125x37mm) blue (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2494	5" (125x37mm) orange (285g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Carbon Castor Wheels (30mm)

		Front Seat Height (FSH) in mm										
	Carbon Castor Wheels (30mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2495	4" (100x30mm) black (158g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2496	5" (125x30mm) black (205g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

04 Rear Wheels / Rear Seat Height (RSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Rear Wheels (incl. Tyres and Push Rims)

Weight is indicated per complete wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT
❑	752	A	Light-Wheel Schwalbe RightRun Light tyres (1" tyre width) Aluminium push rims, black	24"	
❑	2473	A	Blacklight wheel, aluminium, rim/hub/spokes black Schwalbe Marathon Plus tyres (1" width) Aluminium push rims, black	24"	
❑	2466	A	Cross wheel Knobby tyres (1.75" width) Stainless steel push rims	24"	
❑	2461	A	DayLite wheel, aluminium, rim/hub/spokes black Gazelle tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	24"	
❑	2468	B	DayLite wheel, aluminium, rim/hub/spokes black Speedlite tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	25"	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear Wheels (without Tyres and Push Rims)

Tyres and push rims must be selected separately. Weight is indicated per wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT
❑	651	A	Standard wheels, grey	24"	1465g
❑	2651	A	Standard wheels, black	24"	1465g
❑	706	A	Drum brake wheels, 36 radial spokes (stainless steel), drum brake for attendant ⚠ *Only with push handles, long (C-410) or height-adjustable (C-502)* *NC with light pressure brake (C-2595)* *NC with 3° camber (C-447)*	24"	
❑	848	A	Silverdesign, radial spokes, and high-flange hub	24"	870g
❑	695		Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black ⚠ *Recommended for users from 100kg or for dynamic driving style* *NC with PU tyres, puncture-proof (C-474)* *NC with Carbolife push rims (C-849, C-850, C-853)*	24"	
❑	695	B	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black ⚠ *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	25"	
❑	695	C	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black ⚠ *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	26"	
❑	2470	A	Spinergy LX, rim/hub and 12x4mm spokes black ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2471	A	Spinergy LX, rim/hub black, 12x4mm spokes white ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2472	A	Spinergy LX, rim/hub black, 12x4mm spokes orange ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2469	A	Spinergy CLX, carbon rim, hub/18x3mm spokes black ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

05 Tyres

Tyres are made of a rubber compound that may leave permanent or hard-to-remove marks on certain surfaces (plastic, wood, parquet, carpets or rugs). No liability is accepted for abrasion damage. Weight is indicated per tyre.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	496	High-pressure tyre, 8 bar, 1" tyre width	24"	
❑	486	Pneumatic tyre, grooved tread, 4 bar, 1 3/8" tyre width	24"	
❑	902	PU tyre, puncture-proof, 1" tyre width, grey ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	474	PU tyre, puncture-proof, 1" tyre width, black ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	897	Schwalbe Marathon Plus, puncture-resistant, 1" tyre width, black	24"/25"/26"	500g
❑	363	Schwalbe One, puncture-resistant, 1" tyre width, black	24"	
❑	395	Maxxis VN Master Alpha Protect, 10 bar, puncture-resistant, 1" tyre width, black	24"/25"/26"	

06 Push Rims

Weight is indicated per push rim.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	494	Aluminium, silver anodised ⚠ *NC with Active wheel (C-695)*	24"	
❑	487	Aluminium, black anodised	24"	255gr
❑	493	Stainless steel, polished	24"/25"/26"	
❑	445	Titanium ⚠ *NC with Silverdesign (C-848)* *NC with standard wheels (C-651, C-2651)*	24"/25"/26"	364g (24")
❑	168	Optigripp-special push rim for tetraplegics	24"	
❑	849	Curve L, aluminium, black anodised, ergonomic profile ⚠ *NC with Active wheel (C-695)*	24"	
❑	850	Curve L Tetra-Grip, aluminium, black, ergonomic profile with anti-slip coating ⚠ *NC with Active wheel (C-695)*	24"	
❑	853	Gekko, aluminium, black anodised, ergonomic profile with integrated, replaceable silicone lip ⚠ *NC with Active wheel (C-695)*	24"	*750g

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Push Rim Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*	
❑	692	Push rim spacing, narrow	
❑	693	Push rim spacing, wide	

07 Rear Wheels Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	697	Release mechanism for tetraplegics, facilitates removal of the drive wheel ⚠ *Only with Silverdesign (C-848) or Active wheel (C-695)*	
❑	489	Hand and spoke guard, transparent	
❑	2082	Spoke reflectors	
❑	819	Reflectors ⚠ *NC with rear wheels C-752, C-2473, C-2461, C-2468, C-2470, C-2471, C-2472*	

08 Camber

	CODE	DESCRIPTION
❑	478	0°
❑	447	3°

09 Center of Gravity

The measurement is taken from the rear edge of the backrest tube to the wheel axle centre, in millimetres.

	ACTIVE			MEDIUM			PASSIVE	
	1 (115mm)	2 (95mm)	3 (75mm)	4 (55mm)	5 (35mm)	6 (15mm)	7 (-5mm)	8 (-25mm)
Position	❑	❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

10 Footplates

The difference between the front seat height (FSH) and the lower leg length (LLL) must be at least 50mm.

LLL (mm)	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	LLL	DESCRIPTION	WEIGHT
❑	805	A	Two-piece footplates, black plastic, flip-up and height adjustable ⚠ *NC with seat width 320mm (C-32)*	
❑	808	A	Two-piece footplates, black aluminium, flip-up, height/depth and angle adjustable ⚠ *NC with seat width 320mm (C-32)*	
❑	312	A	One-piece footplate, black aluminium profile, flip-up, height/depth and angle adjustable - Depth: 100mm	
❑	315	A	One-piece footplate, black aluminium, flip-up, height/depth and angle adjustable - Depth: 150mm	

Footplates Accessories

	CODE	DESCRIPTION	WEIGHT
❑	359	Calf strap	
❑	823	Heel loops ⚠ *NC with footplate one-piece (C-312, C-315)*	

11 Backrest

	CODE	DESCRIPTION	WEIGHT
❑		Standard backrest, angle-adjustable	
❑	818	Backrest foldable forward onto the seat ⚠ *NC with backrest height < 400mm* *NC with armrests (C-81, C-84)*	

Backrest Height (RH)

The backrest cover is adjustable with hook-and-loop fasteners, and the back height can be adjusted ±60mm in 15mm increments.

	C-620	C-626	C-631	C-632	C-633	C-637
	250mm	300 mm	350mm	400 mm	450mm	500mm
Backrest height	❑	❑	❑	❑	❑	❑

ACTIVE

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Angle

The backrest angle is measured relative to the seat surface: 90° = upright; <90° = tilted forward; >90° = tilted backward.

	Position A	Position B	Position C	Position D	Position E
	80°	85°	90°	95°	100°
Backrest Angle	❑	❑	❑	❑	❑

Backrest Upholstery

	CODE	DESCRIPTION	WEIGHT
❑	235	Textile, black	
❑	292	Mesh fabric, breathable, black	
❑	593	Without backrest cover	

Backrest Upholstery Options

	CODE	DESCRIPTION
❑	2002	Backrest upholstery, 20mm wider
❑	2003	Backrest upholstery, 40mm wider

Backrest Accessories

	CODE	DESCRIPTION	WEIGHT
❑	2032	ErgoSeat Pro thoracic pads, small, pair	

12 Ride® Backs

Please specify the CODE from the RIDE order sheet:

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

13 Push Handles

	CODE	DESCRIPTION	WEIGHT
❑	411	Without push handles	
❑	413	Push handles, short	
❑	410	Push handles, long	
❑	141	Push handles, swiveling	
❑	502	Height-adjustable push handles, mounted on back tube, steplessly adjustable up to 150mm ⚠ *NC with backrest height < 350mm (C-620, C-626)* *The maximum achievable height with height-adjustable push handles is HSH + 564mm*	

14 Arm Supports and Arm Pads

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Weight is indicated per item.

Clothes and Mudguards

	CODE	DESCRIPTION	WEIGHT
❑	304	Clothes guard, carbon, fixed-mounted	
❑	101	Mudguards, plastic, fixed-mounted	269-361g
❑	783	Mudguards, carbon, fixed-mounted	189-270g
❑	100	Mudguard, aluminium, black with cold-protection insert, fixed-mounted	

Armrests

	CODE	DESCRIPTION	WEIGHT
❑	81	Armrest, short pad, height-adjustable with one-hand operation, swing-up, removable and lockable ⚠ *NC with RSH < 450mm* *NC with clothes and mudguards*	
❑	84	Armrest, long pad, height-adjustable with one-hand operation, swing-up, removable and lockable ⚠ *NC with RSH < 450mm* *NC with clothes and mudguards*	
❑	24	Tubular armrest with foam rubber pad, aluminium black, swing-away (side), removable, height-adjustable (with tools), non-locking	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

15 Seat Cushions

Standard hook-and-loop strips are included on the seat upholstery.

	CODE	DESCRIPTION	WEIGHT
❑	560	Seat cushion, 30mm	
❑	561	Seat cushion, 60mm	
❑	7199	Netti Contour, breathable 3D cover	
❑	7195	Seat cushion Netti Precision Active with Easycare+	
❑	7196	Seat cushion Netti Precision Active with Stella+	

Seat Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	833	Safety belt (metal buckle)	

16 Ride® Seat Cushions

Please specify the CODE from the RIDE order sheet:

17 Brakes

	CODE	DESCRIPTION	WEIGHT
❑	305	Pressure brake (push to lock)	
❑	2595	Light pressure brake, aluminium	
❑	60/650	One-hand pressure brake, left (incl. long brake lever, foldable)	
❑	74/650	One-hand pressure brake, right (incl. long brake lever, foldable)	

Brake Options

	CODE	DESCRIPTION	WEIGHT
❑	986	Brake lever extension ⚠ *Only with pressure brake (C-305)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

18 Options

Tipping Aid

	CODE	DESCRIPTION	WEIGHT
❑	309	Tipping aid, pair ⚠ *NC with anti-tippers (C-728, C-729, C-730)*	
❑	4930	Tipping aid, left, swing-away ⚠ *NC with anti-tippers (C-728, C-729)*	
❑	4931	Tipping aid, right, swing-away ⚠ *NC with anti-tippers (C-728, C-730)*	
❑	970	Crutch holder ⚠ *Only with anti-tipper (C-728, C-729, C-730) or tipping-aid (C-309, C-4930, C-4931)*	

Anti-tippers

	CODE	DESCRIPTION	WEIGHT
❑	728	Anti-tippers, pair, swing-away ⚠ *NC with tipping aid (C-309)*	
❑	729	Anti-tipper, left, swing-away ⚠ *NC with tipping aid (C-309, C-4930)*	
❑	730	Anti-tipper, right, swing-away ⚠ *NC with tipping aid (C-309, C-4931)*	

Therapy Table

With 24" rear wheels and a rear seat height of less than 470mm, using the therapy table may limit the armrest height.

	CODE	DESCRIPTION	WEIGHT
❑	929	Therapy table, plastic, transparent, attachable to armrests, suitable for seat widths 400–480 mm ⚠ *Only with armrest, long pad (C-84)*	
❑	930	Therapy table, plastic, dark transparent, slides over armrest pads, for defined seat width ⚠ *Only with armrest, long pad (C-84)*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	