AVANTI

1.736

Allowed user weight

75 kg Frame short (C-351)

135 kg Frame med-short (C-349) / medium (C-352) / long (C-353) up to SW 360mm

160 kg Frame long (C-353) from SW 480mm

Suitable for passenger transport

Tested according to ISO 7176-19 (max. user weight 136 kg)

**nicht i.V. mit Hemi-Lenkgabel CODE 173/4906*



MEYRA GROUP



Up to 12° seat tilt for fine adjustmentoptions



Height-adjustable side panel with one-handed operation



Unique brake with extremely low actuating force



Telescopic and angle-adjust-able back height for ideal ad-aptation to changing medical conditions

Versatile and active

EFFICIENCY

- Compatibility with MEYRA's modular system enables lean warehouse manage-ment
- Safety in spare parts provision through an extensive specialist dealer structure
- High variability without parts exchange
- Demand oriented seat height adjustment even for hemiplegic demands

THERAPEUTIC BENEFIT

- Fine tuned adjustment possibilities
- 3 frame lengths enable very good proportional assignment
- Therapeutically proven accessories in distinctive variety
- Equipment adjustable to the individual demands even for changing disease patterns
- Circumferential building block system

FIELD OF USE

- Adaptive wheelchair for universal everyday use
- Long-term care with high adaptation requirement
- Clinic provision
- Neurological disease patterns
- Geriatric disease patterns
- Reinforced version up to 160 kg and up to seat width 580 mm

● ORDER ❍ COST ESTIMATE ❍ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Standard configuration

- Castor wheel 142 mm solid rubber Soft
- Rear wheels 24"
- Handrim aluminium
- Back strap adjustable, light
- Leg supports, removable and swivelling
- Footrests flip-up, height and angle-adjustable
- Frame colour Silverline
- Adjustable seat belt
- Velcro strap on seat belt

Allowed user weight

75 kg Frame short (C-351)
135 kg Frame med-short (C-349) / medium (C-352) / long (C-353) up to SW 360mm
160 kg Frame long (C-353) from SW 480mm

Suitable for passenger transport

Tested according to ISO 7176-19 (max. user weight 136 kg)
*nicht i.V. mit Hemi-Lenkgabel CODE 173/4906

Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

ACTIVE

Technical specifications

1) When using auxiliary drives, the permissible total weight must not be exceeded

	FRAME SHORT	*RAHMEN MIT./GEK-	FRAME MEDIUM	FRAME LARGE
Seat widths in mm	300 - 360	360 - 580	360 - 580	360 - 580
Width ready to drive in mm from			Seat width + 200mm / with side guard CODE 100 seat width + 180mm	
Width folded in mm from				280
Seat depth in mm	330 - 380	380 - 400	350 - 460	480 - 530
Seat height front/rear in mm	370-500 / 370-470	370 - 560 / 370 - 520	400-560 / 390-520	400-560 / 390-520
Back support height in mm	340 - 500	340 - 500	380 - 440	380 - 440
Arm support height in mm	165 - 240	200 - 290	200 - 290	200 - 290
Length with footrest in mm	880	1010	1040	1120
Length without footrests in mm	660		770	850
User weight	75 kg	135 kg	135 kg	from SW 480 160 kg
Empty weight from	12 kg	13 kg	13 kg	13 kg
Permitted total weight in kg	87 kg	155 kg	148 kg	from SW 480 185 kg [1)]
Transport weight	8 kg	8.5 kg	8.5 kg	9 kg
*Antriebsrad mm/Zoll	510/20 - 560/22	560/22 - 610/24	560/22 - 610/24	560/22 - 610/24
Brake test according to STANDARD				7°

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

01 Frame and Legrests

	CODE	DESCRIPTION	WEIGHT
❑	93	*70° Beinstützen, wegschwenkbar und abnehmbar, Paar ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	759	*70° Beinstütze, wegschwenkbar und abnehmbar, links ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	760	*70° Beinstütze, wegschwenkbar und abnehmbar, rechts ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	293	*78° Beinstützen, wegschwenkbar und abnehmbar, Paar	
❑	92	*Beinstützen, wegschwenkbar, abnehmbar und hochschwenkbar, Paar ⚠ *Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit Einzelfussplatten (C-798)*	
❑	757	*Beinstütze, wegschwenkbar, abnehmbar und hochschwenkbar, links ⚠ *Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit Einzelfussplatten (C-798)*	
❑	758	*Beinstütze, wegschwenkbar, abnehmbar und hochschwenkbar, rechts ⚠ *Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit Einzelfussplatten (C-798)*	
❑	52	*Amputationsbeinstützen, Paar ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	4508	Amputation leg support, left ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	4507	Amputation leg support, right ⚠ *Nicht i.V. mit Rahmen kurz (C-351)*	
❑	94	Without legrests	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	227	Red metallic
❑	224	Blue metallic
❑	4044	Red matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4919	Silverline
❑	4922	Metallic green

02 *Sitzbreite (SB) / Sitztiefe (ST) in Kombination mit Rahmenlänge

FRAME	*KURZ (C-351)			*MIT-KURZ (C-349)		*MITTEL (C-352)					*LANG (C-353)		
	(C-393)	(C-610)	(C-368)	(C-368)	(C-615)	(C-610)	(C-368)	(C-615)	(C-788)	(C-619)	(C-787)	(C-792)	(C-793)
Seat depth in mm	**330 mm**	**350mm**	**380mm**	**380mm**	**400 mm**	**350mm**	**380mm**	**400 mm**	**430 mm**	**460 mm**	**480mm**	**500mm**	**530 mm**
SW 300mm (C-30)	❑	❑	❑										
SW 320mm (C-32)	❑	❑	❑										
SW 340mm (C-34)	❑	❑	❑										
SW 360mm (C-36)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 380mm (C-38)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 400mm (C-40)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 420mm (C-342)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 440mm (C-344)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 460mm (C-46)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
SW 480mm (C-48)					❑			❑	❑	❑	❑	❑	❑
SW 500mm (C-350)					❑			❑	❑	❑	❑	❑	❑
SW 530mm (C-53)					❑			❑	❑	❑	❑	❑	❑
SW 580mm (C-358)					❑			❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Seat widths option

	CODE	DESCRIPTION	SW
❑	4541	Aluminum double crossbrace ⚠ *recommended when using additional drives or high loads*	360 - 460 mm

02 *Lenkräder / Vordere Sitzhöhe (VSH) - Rahmen kurz

		Front Seat Height (FSH) in mm																			
Code	Castor	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560
151	Ø 100 Solid rubber	❑		❑																	
325	Ø 125 Solid rubber			❑			❑	❑	❑	❑	❑	❑	❑	❑							
154	Ø 142 Soft solid rubber							❑	❑	❑	❑	❑	❑	❑	❑						
161	Ø 150 puncture-proof							❑	❑	❑	❑	❑	❑	❑	❑						

02 *Lenkräder / Vordere Sitzhöhe (VSH) - Rahmen mittel-kurz/mittel/lang

		Front Seat Height (FSH) in mm																			
Code	Castor	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560
151	Ø 100 Solid rubber		❑	❑		❑	❑														
325	Ø 125 Solid rubber				❑			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
154	Ø 142 Soft solid rubber									❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
143	Ø 150 puncture-proof										❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
161	Ø 175 puncture-proof												❑	❑	❑	❑	❑	❑	❑	❑	❑
645	Ø 180 pneumatic tyres												❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ *CODE 161 and CODE 645 not i.C. with frame compact CODE 349*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Seat height option

	CODE	DESCRIPTION
❑	4906	HEMI-distancer block for laterally displaced steering fork ⚠ *only in conjunction with fork long CODE 173* *Fork color black anodized*
❑	903	Reinforced steering wheel forks, recommended when using additional drives and higher user weights

Steering wheel tyres

	CODE	DESCRIPTION
❑	908	Tyre black ⚠ *Only i.c. with CODE 151, 325 and 154*
❑	909	Tire grey ⚠ *Only i.c. with CODE 151, 325, 154, 143, 161 and 645*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Castors

	CODE	DESCRIPTION	RIM	TYRES	Ø X W
❑	2480	Lightwheel (pair)	Plastic black	Solid rubber, transparent/coloured	100 x 23 mm
❑	2481	Swivel castor (pair)	Aluminium silver	Solid rubber, black	100 x 32 mm
❑	2482	Swivel castor (pair)	Aluminium silver	Solid rubber, black	125 x 32 mm
❑	2483	Swivel castor	Aluminium silver	Solid rubber, black	100 x 37 mm
❑	2484	Swivel castor	Aluminum black	Solid rubber, black	100 x 37 mm
❑	2485	Swivel castor	Aluminium white	Solid rubber, black	100 x 37 mm
❑	2486	Swivel castor	Aluminium red	Solid rubber, black	100 x 37 mm
❑	2487	Swivel castor	Aluminium blue	Solid rubber, black	100 x 37 mm
❑	2488	Swivel castor	Aluminium orange	Solid rubber, black	100 x 37 mm
❑	2489	Swivel castor	Aluminium silver	Solid rubber, black	125 x 37 mm
❑	2490	Swivel castor	Aluminum black	Solid rubber, black	125 x 37 mm
❑	2491	Swivel castor	Aluminium white	Solid rubber, black	125 x 37 mm
❑	2492	Swivel castor	Aluminium red	Solid rubber, black	125 x 37 mm
❑	2493	Swivel castor	Aluminium blue	Solid rubber, black	125 x 37 mm
❑	2494	Swivel castor	Aluminium orange	Solid rubber, black	125 x 37 mm
❑	2495	Swivel castor	Carbon black	Solid rubber, black	100 x 30 mm
❑	2496	Swivel castor	Carbon black	Solid rubber, black	125 x 30 mm

04 *Hinterräder / Hintere Sitzhöhe (HSH) - Rahmen kurz

		Front Seat Height (FSH) in mm																			
Ø	Width	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560
Ø 20 x 1"	1"	❑		❑																	
Ø 22 x 1"	1"				❑	❑	❑		❑	❑	❑	❑									

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

*Hinterräder / Hintere Sitzhöhe (HSH) - Rahmen mittel-kurz/mittel/lang

		Rear seat height in mm (RSH)																		
Ø	Width	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560
20"	1"	❑	❑	❑																	
22"	1"			❑	❑	❑		❑	❑	❑	❑	❑		❑							
22"	1 3/8"				❑	❑	❑		❑	❑	❑	❑	❑		❑						
24"	1"						❑	❑		❑	❑	❑	❑	❑		❑					
24"	1 3/8"							❑	❑		❑	❑	❑	❑	❑		❑				

Rear Wheels (incl. Tyres and Push Rims)

Weight is indicated per complete wheel (without quick release axle).

	CODE	DESCRIPTION	Ø
❑	2465	Six-Star High-pressure tyres (8bar) Aluminium push rims	24"
❑	752	Light-Wheel Schwalbe RightRun Light tyres (1" tyre width) Aluminium push rims, black	20"/22"/24"
❑	2473	Blacklight wheel, aluminium, rim/hub/spokes black Schwalbe Marathon Plus tyres (1" width) Aluminium push rims, black	24"
❑	2466	Cross wheel Knobby tyres (1.75" width) Stainless steel push rims	24"
❑	2461	DayLite wheel, aluminium, rim/hub/spokes black Gazelle tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	24"
❑	2468	DayLite wheel, aluminium, rim/hub/spokes black Speedlite tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	25"

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Rear Wheels (without Tyres and Push Rims)

Tyres and push rims must be selected separately. Weight is indicated per wheel (without quick release axle).

	CODE	DESCRIPTION	Ø	WEIGHT
❑	706	Drum brake wheels, 36 radial spokes (stainless steel), drum brake for attendant ⚠ *Nicht i.V. mit Druckbremse (C-305)*	24"	
❑	651	Standard wheels, grey	22"/24"	
❑	2651	Standard wheels, black	24"	
❑	848	Silverdesign, radial spokes, and high-flange hub	24"	
❑	695	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black ⚠ *Empfohlen ab 100 kg Nutzergewicht oder bei dynamischer Fahrweise* *Nur i.V. mit Greifreifen Edelstahl (C-493) oder Optigripp (C-168)* *Nicht i.V. mit PU-Breifung (C-902)*	24"	
❑	2470	Spinergy LX, rim/hub and 12x4mm spokes black ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	
❑	2471	Spinergy LX, rim/hub black, 12x4mm spokes white ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	
❑	2472	Spinergy LX, rim/hub black, 12x4mm spokes orange ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	
❑	2469	Spinergy CLX, carbon rim, hub/18x3mm spokes black ⚠ *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	

05 Tyres

Tyres are made of a rubber compound that may leave permanent or hard-to-remove marks on certain surfaces (plastic, wood, parquet, carpets or rugs). No liability is accepted for abrasion damage. Weight is indicated per tyre.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	486	Pneumatic tyre, grooved tread, 4 bar, 1 3/8" tyre width	22"/24"	
❑	902	*PU-Bereifung, pannensicher, Reifenbreite 1" oder 1 3/8", grau ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	22"/24"	
❑	474	PU tyre, puncture-proof, 1" tyre width, black ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	897	Schwalbe Marathon Plus, puncture-resistant, 1" tyre width, black	22"/24"	500g
❑	363	Schwalbe One, puncture-resistant, 1" tyre width, black	24"	
❑	395	Maxxis VN Master Alpha Protect, 10 bar, puncture-resistant, 1" tyre width, black	24"	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

06 Push Rims

Weight is indicated per push rim.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	494	Aluminium, silver anodised ⚠ *NC with Active wheel (C-695)*	22"/24"	
❑	493	Stainless steel, polished	24"	
❑	168	Optigripp-special push rim for tetraplegics ⚠ **Nicht i.V. mit Greifreifenabstand eng (C-692)*	24"	
❑	849	Curve L, aluminium, black anodised, ergonomic profile ⚠ *NC with Active wheel (C-695)*	24"	
❑	850	Curve L Tetra-Grip, aluminium, black, ergonomic profile with anti-slip coating ⚠ *NC with Active wheel (C-695)*	24"	
❑	853	Gekko, aluminium, black anodised, ergonomic profile with integrated, replaceable silicone lip ⚠ *NC with Active wheel (C-695)*	24"	*750g
❑	871	One-arm drive ⚠ **Nicht i.V. mit Sitzbreite < 380mm (C-30, C-32, C-34, C-36) und > 480mm (C-350, C-53, C-358)* *Nur i.V. mit PU-Bereifung 1 3/8" (C-902)* *Nicht i.V. mit Trommelbremse (C-706)* *Nicht i.V. mit Radspritzschutz (C-100)*	24"	

Push Rim Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	166	Silicon hand rim cover, smooth, black ⚠ **Nicht i.V. mit 20" Hinterräder* *Nicht i.V. mit Cross-Rad (C-2466), Aluminium Greifreifen (C-494)*	
❑	692	Push rim spacing, narrow	
❑	693	Push rim spacing, wide	

07 Rear Wheels Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	489	Hand and spoke guard, transparent	
❑	819	Reflectors ⚠ *NC with rear wheels C-752, C-2473, C-2461, C-2468, C-2470, C-2471, C-2472*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

08 Camber

	CODE	DESCRIPTION	WEIGHT
❑	907	3° ⚠ *Nicht i.V. mit Trommelbremse (C-706) Nicht i.V. mit Radstandsverlängerung (C-880) Nicht i.V. mit Doppelgreifreifen (C-871) Nicht i.V. mit Seitenteil mit Armpolster (C-107)	

09 Center of Gravity

- Position A: C-351=22.5mm ; C-349/352/353=30mm
- Position B: C-351=37.5mm ; C-349/352/353=45m
- Position C: C-351=52.5mm ; C-349/352/353=60mm
- Position D: C-349/352/353=75mm

	PASSIVE	MEDIUM		ACTIVE
	A	B	C	D
Position	❑	❑	❑	❑

Wheelbase Extension

	CODE	DESCRIPTION	WEIGHT
❑	880	*Radstandverlängerung (60mm) ⚠ *Nicht i.V. mit Radsturz 3° (C-907) Nur i.V.m. Bremshebelverlängerung CODE 681	

ACTIVE

☐ Please select by ticking the relevant boxes (S) Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

10 *Fussplatten - Rahmen kurz

The difference between the seat height at the front and the lower leg length must be at least 50 mm

*USL K	290	300	310	320	330	340	350	360	370	380	390
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	LLL	DESCRIPTION	WEIGHT
❑	54	A	One-piece footplate, black, flip-up, height/depth (60mm in 4 positions) and angle adjustable - Depth: 150mm	
❑	87	A	One-piece footplate, black, flip-up, height/depth (15mm) and angle adjustable - Depth: 100mm ⚠ *NC with seat width < 480mm (C-350, C-53, C-358)*	
❑	798	A	Two-piece footplates, flip-up, height and angle adjustable - Depth: 160mm ⚠ *NC with seat width < 380mm (C-30, C-32, C-34, C-36)*	
❑	808	A	*Einzelfussplatten in schwarz, hochklappbar, höhen-, tiefen- und winkelverstellbar - Tiefe: 150mm	

10 Footplates - Frame medium-short/medium/long

The difference between the front seat height (FSH) and the lower leg length (LLL) must be at least 50mm.

*USL M/L	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	LLL	DESCRIPTION	WEIGHT
❑	54	A	One-piece footplate, black, flip-up, height/depth (60mm in 4 positions) and angle adjustable - Depth: 150mm	
❑	87	A	One-piece footplate, black, flip-up, height/depth (15mm) and angle adjustable - Depth: 100mm ⚠ *NC with seat width < 480mm (C-350, C-53, C-358)*	
❑	798	A	Two-piece footplates, flip-up, height and angle adjustable - Depth: 160mm ⚠ *NC with seat width < 380mm (C-30, C-32, C-34, C-36)*	
❑	808	A	*Einzelfussplatten aus Kunststoff in schwarz, hochklappbar, höhen-, tiefen- und winkelverstellbar - Tiefe: 150mm	

*Verkürzte Unterschenkellänge - Rahmen mittel-kurz/mittel/lang

*VUSL (mm)	290	300	310	320	330	340	350	360	370	380	390
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	VUSL	DESCRIPTION
❑	3532	A	Leg rest can be removed and swiveled away for shortened lower leg length

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

*Stufenlose Fusstützen- Rahmen mittel-kurz/mittel/lang

	CODE	DESCRIPTION	WEIGHT
❑	2092	*Stufenlose Einstellung Unterschenkellänge ⚠ *Only i.c.w. Leg support CODE 92*	
❑	2093	*Stufenlose Einstellung Unterschenkellänge ⚠ *only in combination with legrest CODE 93*	

Footplates Accessories

	CODE	DESCRIPTION	WEIGHT
❑	822	Toe strap (pair)	
❑	823	Heel loops	
❑	946	*Wadenband für Einzelfussplatten	
❑	359	Calf strap	

11 Backrest

	CODE	DESCRIPTION	WEIGHT
❑	621	Backrest without lumbar support	
❑	622	Backrest with lumbar support ⚠ *Nicht i.V. mit Rücken mit Gasdruckfeder verstellbar (C-26, C-4212)*	
❑	29	*Rücken, winkeleinstellbar (+/- 10° ab Sitzfläche, in 5° Schritten) ⚠ *Nicht i.V. mit Rückenhöhe < 380mm (C-434, C-436)* *Nicht i.V. mit Rücken mit Lumbalknick (C-622)* *Nicht i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

*Rücken mit Gasdruckfeder

	CODE	DESCRIPTION	WEIGHT
❑	4212	*Rücken mit Gasdruckfeder verstellbar, 20° stufenlos ⚠ *Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit Radsturz 3° (C-907)* *Nur i.V. mit Rückenhöhe 420mm (C-442)* *Nur i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)* *Nur i.V. mit Schwerpunkteinstellung A* *Nur i.V. mit Antikipp-Rollen (C-728, C-691)*	
❑	26	*Rücken mit Gasdruckfeder verstellbar, 30° stufenlos ⚠ *Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit Radsturz 3° (C-907)* *Nur i.V. mit Rückenhöhe 420mm (C-442), Schiebestange querliegend (C-814)* *Nur i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)* *Nur i.V. mit Schwerpunkteinstellung A und Radstandsverlängerung (C-880)*	

Backrest Height (RH)

*Der Rückenbezug ist über Klettbänder anpassbar.

	*C-434	*C-436	*C-438	*C-365	*C-442	*C-444	*C-2046	*C-634	C-637
	340mm	360mm	380mm	400 mm	420mm	440mm	460 mm	480mm	500mm
Backrest height	❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ *RH > 400mm (C-442, C-444, C-2046, C-634, C-637) nicht i.V. mit Sitzbreite < 360mm (C-30, C-32, C-34)*
RH > 440mm (C-2046, C-634, C-637) nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)

	CODE	DESCRIPTION	WEIGHT
❑	983	*Teleskopierbare Rückenhöheneinstellung 350-410mm (4 Schritte je 15mm) ⚠ *Nicht i.V. mit Rückenbezug Netzgewebe, atmungsaktiv, schwarz (C-292), ohne Rückenbezug (C-593), Rückenbezug 20mm breiter (C-2002)* *Nicht i.V. mit Rücken mit Lumbalknick (C-622)* *Nicht i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)*	
❑	984	*Teleskopierbare Rückenhöheneinstellung 400-460mm (4 Schritte je 15mm) ⚠ *Nicht i.V. mit Rückenbezug Netzgewebe, atmungsaktiv, schwarz (C-292), ohne Rückenbezug (C-593), Rückenbezug 20mm breiter (C-2002)* *Nicht i.V. mit Rücken mit Lumbalknick (C-622)* *Nicht i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Backrest Upholstery

	CODE	DESCRIPTION	WEIGHT
❑	287	*Polyester, Tiefschwarz	
❑	292	Mesh fabric, breathable, black	
❑	593	Without backrest cover	

Backrest Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	2002	Backrest upholstery, 20mm wider *Nicht i.V. mit Rückenbezug Netzgewebe, atmungsaktiv, schwarz (C-292)* *Nicht i.V. mit C-983 oder C-984*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Accessories

	CODE	DESCRIPTION	WEIGHT
❑	2032	ErgoSeat Pro thoracic pads, small, pair ⚠ *Nicht i.V. mit Rückenbezug 20mm breiter (C-2002)*	
❑	913	*Kopfstütze, 300mm stufenlos höhenverstellbar ⚠ *Nur i.V. mit Schiebestange (C-814)*	

12 Ride System Back

Please specify the CODE from the RIDE order sheet:

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

13 Push Handles

	CODE	DESCRIPTION	WEIGHT
❑	410	Push handles, long	
❑	413	Push handles, short ⚠ **Nicht i.V. mit Schiebestange (C-814)* *Nicht i.V. mit Trommelbremse (C-706)*	
❑	502	*Höhenverstellbare Schiebegriffe, am Rückenrohr montiert, stufenlos bis 170mm ⚠ **Nicht i.V. mit Rückenhöhe > 440mm (C-2046, 634, C-637)* *Nicht i.V. mit Schiebestange (C-814), Stabilisierungsbügel (C-238)*	

*Schiebestange und Stabilisierungsbügel

	CODE	DESCRIPTION	WEIGHT
❑	814	Horizontal push bar, stabilises the back support under heavy strain ⚠ **Nicht i.V. mit Schiebegriffe kurz (C-413), höhenverstellbare Schiebegriffe (C-502)*	
❑	238	Stabilising bracket for the back support, folding ⚠ **Nicht i.V. mit SB 300mm (C-30)* *Nicht i.V. mit Rückengurt mit teleskopierbare Rückenhöheneinstellung (C-983, C-984)* *Nicht i.V. mit höhenverstellbare Schiebegriffe (C-502)*	

14 Arm Supports and Arm Pads

*Die Sitzbreite wird zwischen den Aussenrohren der Sitzbespannung gemessen. Je nach gewählten Seitenteilen und Armlehnen kann die effektive Sitzbreite um bis zu +/- xx mm abweichen. Die Rückenbreite entspricht der Sitzbespannungsbreite und wird unten an den Aussenrohren gemessen. Das Gewicht ist pro Stück angegeben.

Clothes and Mudguards

	CODE	DESCRIPTION	WEIGHT
❑	100	*Radspritzschutz (Radüberdeckung 35mm), Aluminium, schwarz mit Kälteschutzeinlage (Carbonoptik-Folie aus Kunststoff), fest verschraubt ⚠ **Nicht i.V. mit Schwerpunkteinstellung A (passiv)* *Nicht i.V. mit Rücken, winkeleinstellbar (C-29)*	
❑	98	*Radspritzschutz (Radüberdeckung 50mm), Aluminium, schwarz mit Kälteschutzeinlage (Carbonoptik-Folie aus Kunststoff), fest verschraubt ⚠ **Nicht i.V. mit Schwerpunkteinstellung A (passiv)* *Nicht i.V. mit Rücken, winkeleinstellbar (C-29)* *Empfohlen i.V. mit Trommelbremse (C-706)*	
❑	748	*Radspritzschutz, Aluminium, schwarz mit Kälteschutzeinlage (Carbonoptik-Folie aus Kunststoff), inkl. Armlehnen, höhenverstellbar (mit Schrauben), fest verschraubt ⚠ **Nicht i.V. mit Schwerpunkteinstellung A (passiv)* *Nicht i.V. mit Rücken, winkeleinstellbar (C-29)* *Therapietischtauglich nur i.V. mit Rahmen kurz (C-351)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Armrests

	CODE	DESCRIPTION	WEIGHT
❑	81	Armrest, short pad, height-adjustable (with or without tools depending on frame), swing-up, removable and lockable ⚠ **C-351 mit Werkzeug einstellbar; C-349/352/353 ohne Werkzeug verstellbar*	
❑	84	Armrest, long pad, height-adjustable (with or without tools depending on frame), swing-up, removable and lockable ⚠ **Nicht i.V. mit Rahmen kurz (C-351)*	
❑	21	Reinforced armrest, extra-long pad, height-adjustable, swing-up, removable and lockable ⚠ **Nicht i.V. mit Rahmen kurz (C-351)*	
❑	107	Armrest, extra-long pad, height-adjustable with one-hand operation, depth-adjustable, swing-up, removable and lockable ⚠ **Nicht i.V. mit Rahmen kurz (C-351), mittel-kurz (C-349)* *Nicht i.V. mit HSH < 450mm* *Nicht i.V. mit Schwerpunkteinstellung C/D (mittel/aktiv)* *Nicht i.V. mit Rücken, winkeleinstellbar (C-29)* *Nicht i.V. mit Einhanddruckbremse (C-60/650, 74/650)* *Nicht i.V. mit Cross-Rad (C-2466)*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

15 Seat Cushions

	CODE	DESCRIPTION	WEIGHT
❑	560	Seat cushion, 30mm	
❑	561	Seat cushion, 60mm	
❑	7199	Netti Contour, breathable 3D cover	

Seat Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	833	Safety belt (metal buckle)	

16 Ride System Seat

Please specify the CODE from the RIDE order sheet:

17 Brakes

	CODE	DESCRIPTION	WEIGHT
❑	305	Pressure brake (push to lock) ⚠ **Nicht i.V. mit Trommelbremsrad (C-706)*	
❑	60/650	One-hand pressure brake, left (incl. long brake lever, foldable) ⚠ **Nicht i.V. mit Doppelgreifreifen rechts (C-871/74)* *Nicht i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)*	
❑	74/650	One-hand pressure brake, right (incl. long brake lever, foldable) ⚠ **Nicht i.V. mit Doppelgreifreifen links (C-871/60)* *Nicht i.V. mit Seitenteil über Einhandbedienung höhenverstellbarer Armlehne (C-107)*	

Brake Options

	CODE	DESCRIPTION	WEIGHT
❑	681	Brake lever extension, foldable, fixed-mounted ⚠ *Only in conjunction with brake CODE 305 or 706*	
❑	986	Brake lever extension ⚠ *Only with pressure brake (C-305)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

18 Options

	CODE	DESCRIPTION	WEIGHT
❑	912	Air-pump with holder	
❑	936	Sliding board, plastic for repositioning	
❑	679	Folding lock	

Anti-tippers

	CODE	DESCRIPTION	WEIGHT
❑	728	*Antikipp-Rollen, wegschwenkbar, Paar ⚠ *Nicht i.V. mit HSH < 410mm*	
❑	729	*Antikipp-Rolle, wegschwenkbar, links ⚠ *Nicht i.V. mit HSH < 410mm*	
❑	730	*Antikipp-Rolle, wegschwenkbar, rechts ⚠ *Nicht i.V. mit HSH < 410mm*	
❑	691	*Antikipp-Rollen, einsteckbar und abnehmbar, Paar ⚠ *Nur i.V. mit Kipphilfe (C-309)*	
❑	712	*Antikipp-Rolle, einsteckbar und abnehmbar, links ⚠ *Nur i.V. mit Kipphilfe (C-309, C-4930)*	
❑	713	*Antikipp-Rolle, einsteckbar und abnehmbar, rechts ⚠ *Nur i.V. mit Kipphilfe (C-309, C-4931)*	
❑	747	*Rangierrollen, Paar ⚠ *Nicht i.V. mit Antikipp-Rollen wegschwenkbar (C-728, C-729, C-730)*	

Tipping Aid

	CODE	DESCRIPTION	WEIGHT
❑	309	Tipping aid, pair	
❑	4930	Tipping aid, left, swing-away	
❑	4931	Tipping aid, right, swing-away	
❑	970	Crutch holder ⚠ *Nur i.V. mit Auftrittrohr (C-309, C-4930, C-4931)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Therapy tables

*Bei 24" Hinterrädern und einer hinteren Sitzhöhe kleiner als 470mm ergibt sich beim Einsatz des Therapietisches (C-929, C-930) eine Einschränkung der Armlehnenhöhe.

	CODE	DESCRIPTION	WEIGHT
❑	929	*Therapietisch, Kunststoff, transparent, aufschiebbar, passend für SB von 400 bis 580 mm ⚠ *only in conjunction with side panel CODE 21 / CODE 84/ CODE 107 with frame middle or long* *only in conjunction with side panel CODE 81 with frame short*	
❑	930	Therapy table, plastic, dark transparent, slides over armrest pads, for defined seat width ⚠ *from seat width 380mm possible* *only in conjunction with side panel CODE 21, CODE 84 or CODE 107* *not in conjunction with. Frame short CODE 351*	
❑	4662	Therapy table, half-sided left, plastic, transparent, ergonomically formed ⚠ *Only in conjunction with side panel CODE 21 / CODE 84 or CODE 107* *not in conjunction with frame short CODE 351*	
❑	4663	Therapy table, half-sided right, plastic, transparent, ergonomically formed ⚠ *Only in conjunction with side panel CODE 21 / CODE 84 or CODE 107* *not in conjunction with frame short CODE 351*	

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	



14 Code 21



10 Code 26



15 Code 52



15 Code 54



15 Code 87



15 Code 92




14 Code 98



14 Code 107



00 Code 174



08 Code 305




10 Code 410




10 Code 413



00 Code 418



10 Code 621



10 Code 622



08 Code 650



08 Code 681



19 Code 691



14 Code 748



15 Code 798



03 Code 880



10 Code 4212



15 Code 4312