CL409

1.254 Stock version

Allowed user weight

136 kg

MEYRA QUALITY TESTED



ORTOPEDIA

EINE MARKE VON MEYRA



LED technology



Simple user guidance



Extremely robust cassette-type frame



Spring-loaded comfort seating system

The reliable one

ADAPTATION

- The angle of the backrest, back extension and height of the seat and armrests are adjustable
- The seat width can be stepless adjusted via the armrests
- The seat has adjustment rails and can be rotated through 360°

OPERATION

- Very easy to use
- Manual smooth steering
- Driving lever for thumb operation and finger operation
- Mechanical release of the spring-loaded brake
- Self-explanatory control panel with speed preselection options

● ORDER ❍ COST ESTIMATE ❍ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

ORTOPEDIA
EINE MARKE VON MEYRA



Standard configuration

- alloy wheels
- 2 x rearview mirrors
- Reversible and lockable handlebar
- spring-loaded comfort seat
- Height- und angle-adjustable backrest, rotatable about 360°
- seat adjustment
- Swing-up armrests
- Double lever for thumb operation
- Lighting including turn signal, hazard warning light and brake light
- self-explanatory Display
- Sensor
- Battery charger

Allowed user weight

136 kg

Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply

Valid from 01.01.2026 – 31.12.2026.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

SCOOTER

Technical specifications

Length in mm	1200
Width in mm	610
Seat widths in mm	420 - 480
Seat depth in mm	410
Seat width adjustable in mm	450 - 670
Back support height in mm	450
Transport height (with folded-down steering column and without seat)	600
Castor wheels diameter	260
Drive wheels diameter	260
Ground clearance in mm	100
Max. obstacle height in mm	60
Turning radius in mm	1500
Continuous motor performance	210 W
Peak motor performance	850 W
Batteries	2x 12V 35 Ah
Battery charger	4 A
Electronic	70 A
Range	30 km
Permitted inclination/slopes	9° / 16%
Empty weight from	91 kg
User weight	136 kg
Permitted total weight in kg	230 kg
Driving speed	6 km/h

Please enter your quantities in the boxes

01 City liner

Item	DESCRIPTION
9125402	6 km / h - blue metallic
9125422	6 km/h - blue metallic for bus transport
9125405	6 km / h - seaberry metallic

02 Options

Item	DESCRIPTION
3086642	Crutch holder
3075902	Body sack
1058996	Shopping basket additionally, not in combination with walking aid holder Code 3086642