SERVICE

3.600 Stock version

Allowed user weight

120 kg



For universal application

EFFICIENCY

- Quick and dependable spare parts provision, secured in the long term through an expansive specialist dealer network
- Extraordinary durability, little need for repairs

THERAPEUTIC BENEFIT

- For non permanent application (e.g. after an operation) as transport- and mobility aid

FIELD OF USE

- As transport- or pushing aid in hospitals, clinics and in home care
- Transport of guests with reduced mobility, e.g. in the hotel
- For short term use at home or after injuries due to an accident
- As walking aid (scutteling while sitting in a wheelchair)

● ORDER ○ COST ESTIMATE ○ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

MEYRA

MEYRA QUALITY TESTED



Standard configuration

- Drive wheel, puncture-proof, removable, quick-release axle, pressure brake
- Aluminium handrim with 15 mm distance
- Steering wheel puncture safe 200 x 50 mm
- Arm support slanted in the front with padded arm support
- Leg supports, removable and swivelling
- Incl. pedal tube
- Back straps height 400 mm
- Seat height 520 mm
- Seat depth 440 mm
- Chrome version with synthetic leather covers (only i.c. with SW 450 mm)
- including calf strap, continuous
- Colour: Chrome or Silverline

Allowed user weight

120 kg

Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026
Errors, misprints and changes reserved.

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.
When using auxiliary drives, the permissible total weight must not be exceeded.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

MANUAL

Technical specifications

Seat widths in mm	400 / 450 / 480 / 510
Width ready to drive in mm from	620 / 670 / 700 / 730
Width folded in mm from	310
Seat depth in mm	440
Seat height front/rear in mm	520 / 490
Overall height in mm	920
Back support height in mm	400
Arm support height in mm	240
Length with footrest in mm	1080
Length without footrests in mm	780
User weight	120 kg
Empty weight from	19 kg
Permitted total weight in kg	140 kg
Rear wheel	610 mm(24 inch)
Transport weight	11 kg
Brake test according to STANDARD	7°

MANUAL

Please enter your quantities in the boxes

01 Clinic version

Item	DESCRIPTION
9769230	Chrome/ Imitation leather in SW 450 mm

02 Pressure brake (push to lock)

Item	DESCRIPTION
9769075	Pressure brake Silverline/Textile black in SW 400 mm
9769073	Pressure brake Silverline/Textile black in SW 450 mm
9769076	Pressure brake Silverline/Textile black in SW 480 mm
9761783	Pressure brake Silverline/Textile black in SW 510 mm